

View Online at <https://aerobasegroup.com/nsn/5930-01-094-7863>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

15.813 inches

Overall Height:

9.000 inches

Overall Width:

4.750 inches

First Flat Length:

1.125 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

4.625 inches single actuator

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility and 0.410 inches single mounting facility

Individual Section Quantity:

11

Knob Manufacturer Code:

82121

Longest Horizontal Distance Between Mounting Centers:

3.750 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

5.250 inches 2nd mounting facility

End Application:

Multi-hull 03950

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 each section rear

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Rotor Through Connection Quantity:

1 9th section

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 9th section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

60.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0