## NSN 5930-01-094-9967

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-094-9967

**Thread Class:** 2a single mounting facility **Thread Length:** 0.500 inches single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 2.437 inches **Overall Height:** 4.204 inches **Overall Width:** 1.620 inches **Shaft Diameter:** 7.3 millimeters single actuator **Shaft Length:** 0.692 inches single actuator **Individual Section Quantity:** 1 **Longest Horizontal Distance Between Mounting Centers:** 1.156 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.340 inches single mounting facility **Operating Tempurature Range:** -12.0/+121.0 degrees celsius **End Application:** 4920-01-059-8960 **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded stud single mounting facility **Features Provided:** Metallic inclosure and cam actuated **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 600.0 ac at sea level **Mounting Facility Pattern:** Two position diagonal single mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator

**Shaft Type:** 

Round, slotted single actuator

## NSN 5930-01-094-9967

Rotary Switch - Page 2 of 2



Terminal Type:
Screw
Contact Load Current Rating:
6.0 amperes resistive load ac at sea leve
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unf single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0