

View Online at <https://aerobasegroup.com/nsn/5930-01-095-1587>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

1.100 inches

**Overall Height:**

Between 2.420 inches and 2.470 inches

**Overall Width:**

0.930 inches

**Bushing Length:**

0.470 inches

**Body Length:**

1.100 inches

**Body Width:**

0.930 inches

**Case Material:**

Plastic

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.850 inches and 0.900 inches

**Actuator Width:**

0.300 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Actuator Color:**

White single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Ef111a aircraft tac 26512

**Mounting Surface To Terminal End Distance:**

1.100 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

6 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 4.000 amperes motor dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 3.300 amperes motor ac

**Special Features:**

Flexible insulator

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

18 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0