

View Online at <https://aerobasegroup.com/nsn/5930-01-095-1587>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

1.100 inches

Overall Height:

Between 2.420 inches and 2.470 inches

Overall Width:

0.930 inches

Bushing Length:

0.470 inches

Body Length:

1.100 inches

Body Width:

0.930 inches

Case Material:

Plastic

Actuator Style:

Rectangular

Actuator Height:

Between 0.850 inches and 0.900 inches

Actuator Width:

0.300 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Ef111a aircraft tac 26512

Mounting Surface To Terminal End Distance:

1.100 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

6 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 4.000 amperes motor dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 3.300 amperes motor ac

Special Features:

Flexible insulator

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

18 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0