

View Online at <https://aerobasegroup.com/nsn/5930-01-095-1588>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof and corrosion resistant

Overall Length:

1.000 inches

Overall Height:

3.440 inches

Overall Width:

1.000 inches

Body Diameter:

1.000 inches

Bushing Length:

0.470 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Color:

Silver single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Ef111a aircraft tac 26512

Mounting Surface To Terminal End Distance:

2.280 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Holding solenoid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 2.000 amperes inductive dc

Special Features:

Two terminals for magnetic hold-in coil

Test Data Document:

81349-mil-s-5594 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 turret

Specification Data:

81349-mil-s-5594/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0