NSN 5930-01-095-2022

Push Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-095-2022 |
|---|
| Body Style: |
| Bushing mounted |
| Overall Length: |
| 0.500 inches |
| Overall Height: |
| 1.031 inches |
| Overall Width: |
| 0.450 inches |
| Bushing Length: |
| 0.250 inches |
| Body Length: |
| 0.500 inches |
| Body Width: |
| 0.450 inches |
| Body Height: |
| 0.470 inches |
| Case Material: |
| Plastic |
| Actuator Diameter: |
| 0.122 inches |
| Actuator Height: |
| 0.230 inches |
| Actuator Color: |
| Silver single actuator |
| Maximum Voltage Rating In Volts: |
| 20.0 ac and 20.0 dc |
| End Application: |
| 4920-01-040-7816 |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| |

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 400.000 milliamperes resistive ac

Precious Material And Location:

Contact surfaces gold

NSN 5930-01-095-2022

Push Switch - Page 2 of 2



| inread Series Designator: |
|-----------------------------|
| Uns |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0