NSN 5930-01-095-3833

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-095-3833

Body Style:
Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Overall Height:
0.531 inches
Overall Width:
0.438 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.438 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.125 inches
Actuator Style:
Rectangular
Actuator Height:
0.093 inches
Actuator Width:
0.125 inches
Actuator Free Position Height:
0.437 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, double make, momentary action single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:
5.0 ounces

NSN 5930-01-095-3833

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes lamp dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0