

View Online at <https://aerobasegroup.com/nsn/5930-01-095-6125>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

2.070 inches

**Overall Height:**

0.620 inches

**Overall Width:**

0.620 inches

**Body Diameter:**

0.620 inches

**Bushing Length:**

0.440 inches

**Body Length:**

1.000 inches

**Case Material:**

Metal

**Actuator Diameter:**

0.380 inches

**Actuator Height:**

0.280 inches

**Actuator Color:**

Red single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.500 amperes inductive dc and 500.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 500.000 milliamperes lamp ac

**Special Features:**

0.750 in. Dress ring

**Precious Material And Location:**

Terminals and contacts gold

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

6 tab, solder lug

**Specification Data:**

81349-mil-s-8805/75 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0