## NSN 5930-01-095-7701

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-095-7701
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
5.813 inches
Overall Height:
2.812 inches
Overall Width:
2.812 inches
Shaft Length:
1.219 inches single actuator
Individual Section Quantity:
7
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Longest Horizontal Distance Between Mounting Centers:
2.297 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.297 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section rear
Throw Quantity:
6 each section rear
Mounting Method:
Base single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
30.0 dc at sea level
Mounting Facility Pattern:

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

6 single actuator

## NSN 5930-01-095-7701

Rotary Switch - Page 2 of 2



Shaft Type:
Rectangular/square, threaded hole single actuator
Criticality Code Justification:
Feat
Square Shaft Size:
0.250 inches single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
22.5 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Special Features:
Item must comply with requirements of desc production standard no. L02890; for navy nuclear propulsion plant products only
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0