

View Online at <https://aerobasegroup.com/nsn/5930-01-095-9813>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Explosion proof and humidity resistant

**Overall Length:**

3.266 inches

**Overall Height:**

0.750 inches

**Overall Width:**

0.750 inches

**Body Width:**

0.750 inches

**Body Height:**

0.750 inches

**Case Material:**

Metal

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.270 inches

**Actuator Width:**

0.620 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Natural single actuator

**Actuator Inscription:**

Time tab single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Mounting Surface To Terminal End Distance:**

2.996 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal and full display lens and rfi shielding

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

1 socket, integrated wire termination

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0