

View Online at <https://aerobasegroup.com/nsn/5930-01-095-9823>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Overall Length:**

0.906 inches

**Overall Height:**

2.313 inches

**Overall Width:**

1.031 inches

**Bushing Length:**

0.750 inches

**Body Length:**

0.906 inches

**Body Width:**

0.500 inches

**Body Height:**

1.219 inches

**Case Material:**

Metal

**Actuator Height:**

0.344 inches

**Maximum Voltage Rating In Volts:**

14.0 dc

**End Application:**

2420-66-148-7692, hmee (high mobility engineer excavator); mrap buffalo mk2a2

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

2 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0