

View Online at <https://aerobasegroup.com/nsn/5930-01-096-0059>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof and corrosion resistant

Overall Length:

Between 2.470 inches and 2.500 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Bushing Length:

Between 0.969 inches and 1.031 inches

Body Length:

1.200 inches

Body Width:

1.000 inches

Body Height:

1.000 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.213 inches and 0.223 inches

Actuator Height:

Between 0.269 inches and 0.301 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

F14 aircraft 26512

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

160.0 ounces

Actuator Movement:

Between 0.200 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Resilient sealed

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0