

View Online at <https://aerobasegroup.com/nsn/5930-01-096-0059>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Dustproof and corrosion resistant

**Overall Length:**

Between 2.470 inches and 2.500 inches

**Overall Height:**

1.000 inches

**Overall Width:**

1.000 inches

**Bushing Length:**

Between 0.969 inches and 1.031 inches

**Body Length:**

1.200 inches

**Body Width:**

1.000 inches

**Body Height:**

1.000 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.213 inches and 0.223 inches

**Actuator Height:**

Between 0.269 inches and 0.301 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

F14 aircraft 26512

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

16.0 ounces

**Switch Actuating Force:**

160.0 ounces

**Actuator Movement:**

Between 0.200 overtravel inches and 0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

**Special Features:**

Resilient sealed

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0