

View Online at <https://aerobasegroup.com/nsn/5930-01-096-1526>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.575 inches

Overall Height:

2.125 inches

Overall Width:

0.556 inches

Bushing Length:

Between 0.413 inches and 0.485 inches

Body Length:

0.575 inches

Body Width:

0.556 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.375 inches

Actuator Height:

Between 0.850 inches and 0.900 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.740 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0