

View Online at <https://aerobasegroup.com/nsn/5930-01-096-7772>

Hazardous Locations/environmental Protection:

Dustproof and moisture proof

Overall Height:

0.605 inches

Body Diameter:

0.605 inches

Body Height:

0.290 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Distance Between Mounting Facility Centers:

0.937 inches

End Application:

Tran rectific 97520

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -80.0 degrees fahrenheit and 550.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case and tamper proof cap

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.5 amperes resistive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

228.00 actuation point degrees fahrenheit and 248.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0