

View Online at <https://aerobasegroup.com/nsn/5930-01-096-8074>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

Between 4.730 inches and 4.850 inches

First Flat Length:

0.250 inches all actuators

Flat Height:

0.214 inches 1st actuator

Shaft Diameter:

0.248 inches 1st actuator and 0.252 inches 1st actuator

Shaft Length:

0.390 inches 2nd actuator

Individual Section Quantity:

5

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Temperature Range:

-55.0/+85.0 degrees celsius

End Application:

Ef111a aircraft tac 26512

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

8 each section front

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

72.0 degrees from contact position 1 all actuators

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

8 all actuators

Shaft Type:

Round, flatted 2nd actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section front

Switch Actuator Positioning Increment:

36.0 degrees all actuators

Detent Rotational Torque Range:

+0.500/+5.000 inch-pounds all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level and 50.0 amperes inductive load dc at sea level

Special Features:

Add-a-pot

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0