

View Online at <https://aerobasegroup.com/nsn/5930-01-096-8081>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

Between 0.770 inches and 0.850 inches

Overall Height:

2.290 inches

Overall Width:

Between 1.010 inches and 1.090 inches

Bushing Length:

0.470 inches

Body Length:

Between 0.770 inches and 0.850 inches

Body Width:

Between 1.010 inches and 1.090 inches

Body Height:

0.820 inches

Case Material:

Plastic

Actuator Style:

Rectangular

Actuator Height:

0.900 inches

Actuator Width:

0.180 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained and left position momentary and right position momentary

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Ef 111a aircraft tac 26512

Mounting Surface To Terminal End Distance:

0.920 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Precious Material And Location:

Contacts and terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0