

View Online at <https://aerobasegroup.com/nsn/5930-01-096-8081>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

Between 0.770 inches and 0.850 inches

**Overall Height:**

2.290 inches

**Overall Width:**

Between 1.010 inches and 1.090 inches

**Bushing Length:**

0.470 inches

**Body Length:**

Between 0.770 inches and 0.850 inches

**Body Width:**

Between 1.010 inches and 1.090 inches

**Body Height:**

0.820 inches

**Case Material:**

Plastic

**Actuator Style:**

Rectangular

**Actuator Height:**

0.900 inches

**Actuator Width:**

0.180 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained and left position momentary and right position momentary

**Actuator Color:**

White single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Ef 111a aircraft tac 26512

**Mounting Surface To Terminal End Distance:**

0.920 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

**Precious Material And Location:**

Contacts and terminal surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0