

View Online at <https://aerobasegroup.com/nsn/5930-01-096-8084>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

0.575 inches

Overall Height:

2.440 inches

Overall Width:

0.535 inches

Bushing Length:

0.470 inches

Body Length:

0.575 inches

Body Width:

0.535 inches

Body Height:

0.640 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.428 inches

Actuator Height:

1.160 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

End Application:

T sec/kg84 98230

Mounting Surface To Terminal End Distance:

0.810 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0