

View Online at <https://aerobasegroup.com/nsn/5930-01-096-8541>

**Thread Class:**

2a single threaded bushing

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.375 inches

**Body Diameter:**

0.665 inches

**Body Length:**

2.000 inches

**End Application:**

Gmls mk13 mod 44114

**Tempurature Sensing Element Type:**

Bulb

**Width Across Flats:**

1.000 inches

**Mounting Method:**

Threaded bushing

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

16 single threaded bushing

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.750 inches single threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

250.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

175.00 actuation point degrees fahrenheit and 155.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

115.0 ac at sea level single voltage

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas

**Precious Material And Location:**

Contacts and terminal surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Cylindrical w/flange

**Thread Series Designator:**

Unf single threaded bushing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0