

View Online at <https://aerobasegroup.com/nsn/5930-01-096-8541>

Thread Class:

2a single threaded bushing

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.375 inches

Body Diameter:

0.665 inches

Body Length:

2.000 inches

End Application:

Gmls mk13 mod 44114

Tempurature Sensing Element Type:

Bulb

Width Across Flats:

1.000 inches

Mounting Method:

Threaded bushing

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

16 single threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.750 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

250.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

175.00 actuation point degrees fahrenheit and 155.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0