NSN 5930-01-097-1490

Thermostatic Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-097-1490 |
|---|
| Hazardous Locations/environmental Protection: |
| Dustproof and moisture proof |
| Overall Length: |
| 1.203 inches |
| Overall Height: |
| 0.605 inches |
| Body Diameter: |
| 0.605 inches |
| Body Height: |
| 0.290 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Distance Between Mounting Facility Centers: |
| 0.937 inches |
| End Application: |
| Tran rectif 97520 |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Operating Tempurature Rating: |
| Between -80.0 degrees fahrenheit and 550.0 degrees fahrenheit |
| Mounting Method: |
| Bracket and unthreaded hole |
| Features Provided: |
| Hermetically sealed case and tamper proof cap |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 5.5 amperes resistive load third voltage |
| Contact Adjustability: |
| Deactuation point not adjustable and actuation point not adjustable |
| Contact Voltage Rating In Volts: |
| 30.0 dc at sea level third voltage |
| Media For Which Designed: |

Gas

Precious Material And Location:

Contacts silver

NSN 5930-01-097-1490

Thermostatic Switch - Page 2 of 2



| Precious Material: |
|--------------------|
| Silver |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A048b0