

View Online at <https://aerobasegroup.com/nsn/5930-01-097-1839>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

0.860 inches

Overall Height:

2.235 inches

Overall Width:

0.720 inches

Bushing Length:

0.470 inches

Body Length:

0.860 inches

Body Width:

0.720 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.360 inches

Actuator Height:

0.640 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

F111f ptp 81755

Mounting Surface To Terminal End Distance:

1.125 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Specification Data:

81349-mil-s-8805/26 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0