## NSN 5930-01-097-4697

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-097-4697

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
0.750 inches
Overall Height:
3.660 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator
Black single actuator and black single actuator
Black single actuator and black single actuator  Illuminated Actuator Color:
Black single actuator and black single actuator  Illuminated Actuator Color:  Green single actuator and yellow single actuator
Black single actuator and black single actuator  Illuminated Actuator Color:  Green single actuator and yellow single actuator  Actuator Inscription:
Black single actuator and black single actuator  Illuminated Actuator Color:  Green single actuator and yellow single actuator  Actuator Inscription:  On fail single actuator
Black single actuator and black single actuator  Illuminated Actuator Color:  Green single actuator and yellow single actuator  Actuator Inscription:  On fail single actuator  Maximum Voltage Rating In Volts:
Black single actuator and black single actuator  Illuminated Actuator Color:  Green single actuator and yellow single actuator  Actuator Inscription:  On fail single actuator  Maximum Voltage Rating In Volts:  28.0 dc
Black single actuator and black single actuator  Illuminated Actuator Color:  Green single actuator and yellow single actuator  Actuator Inscription:  On fail single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type:
Black single actuator and black single actuator  Illuminated Actuator Color:  Green single actuator and yellow single actuator  Actuator Inscription:  On fail single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type:  Fully enclosed
Black single actuator and black single actuator  Illuminated Actuator Color:  Green single actuator and yellow single actuator  Actuator Inscription:  On fail single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:
Black single actuator and black single actuator  Illuminated Actuator Color:  Green single actuator and yellow single actuator  Actuator Inscription:  On fail single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Panel
Black single actuator and black single actuator  Illuminated Actuator Color:  Green single actuator and yellow single actuator  Actuator Inscription:  On fail single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Panel  Features Provided:
Black single actuator and black single actuator  Illuminated Actuator Color:  Green single actuator and yellow single actuator  Actuator Inscription:  On fail single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Panel  Features Provided:  Holding solenoid

**Contact Load Current Rating At Maximum Rated Voltage:** 

7.000 amperes resistive dc and 3.000 amperes inductive dc

## NSN 5930-01-097-4697

Push Switch - Page 2 of 2



Terminal Type A	nd Quantity:
-----------------	--------------

17 solderless lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0