## NSN 5930-01-097-5910

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-097-5910

**Body Style:** 

Panel mounted

**Overall Length:** 

2.450 inches

**Overall Height:** 

1.000 inches

**Overall Width:** 

0.750 inches

**Body Width:** 

0.655 inches

**Body Height:** 

0.905 inches

Actuator Length:

0.680 inches

Actuator Style:

### Rectangular

Actuator Height:

0.188 inches

Actuator Width:

0.430 inches

Actuator Color:

Yellow single actuator

Illuminated Actuator Color:

Yellow single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.200 inches

Inclosure Type:

Fully enclosed

**Mounting Method:** 

Panel

#### Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.500 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac

#### **Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

9 tab, solder lug

Specification Data:

813/10-mil-c-22885/58 government energification

# NSN 5930-01-097-5910

Push Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

