

View Online at <https://aerobasegroup.com/nsn/5930-01-097-6668>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.612 inches

Overall Height:

1.278 inches

Overall Width:

0.505 inches

Bushing Length:

0.315 inches

Body Length:

0.612 inches

Body Width:

0.505 inches

Body Height:

0.354 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Height:

0.413 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Color:

Silver single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Multi class a 23259

Mounting Surface To Terminal End Distance:

0.550 inches

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Terminal surfaces gold and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0