NSN 5930-01-097-6668



Toggle Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-097-6668 **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 0.612 inches **Overall Height:** 1.278 inches **Overall Width:** 0.505 inches **Bushing Length:** 0.315 inches **Body Length:** 0.612 inches **Body Width:** 0.505 inches **Body Height:** 0.354 inches **Case Material:** Plastic **Actuator Style:** Round **Actuator Height:** 0.413 inches **Actuator Position-action Relationship:** Up position momentary and down position momentary and center position maintained **Actuator Color:** Silver single actuator **Maximum Voltage Rating In Volts:** 250.0 ac and 28.0 dc **End Application:** Multi class a 23259 **Mounting Surface To Terminal End Distance:**

0.550 inches

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

NSN 5930-01-097-6668

Toggle Switch - Page 2 of 2



Contact Load Current Rating	At Maximum	Rated \	/oltage:
-----------------------------	------------	---------	----------

4.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Terminal surfaces gold and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0