

View Online at <https://aerobasegroup.com/nsn/5930-01-097-7271>

Thread Class:

2a 1st mounting facility

Thread Length:

0.250 inches 1st mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

10.312 inches

Overall Height:

6.750 inches

Overall Width:

6.750 inches

First Flat Length:

1.375 inches single actuator

Shaft Diameter:

0.625 inches single actuator

Shaft Length:

2.000 inches single actuator

Unthreaded Mounting Hole Diameter:

0.525 inches 2nd mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

5.625 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

5.625 inches 2nd mounting facility

End Application:

Panel rod mot 94197

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

4 each section periphery

Mounting Method:

Threaded bushing 1st mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 1st mounting facility

Thread Size:

0.750 inches 1st mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 amperes resistive load ac at sea level

Special Features:

Four seal bolts

Style Designator:

Tap, circuit selector

Thread Series Designator:

Un 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0