NSN 5930-01-097-7275

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-097-7275

| Body Style: |
|---|
| Hole mounted |
| Overall Length: |
| 1.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.125 inches |
| Overall Width: |
| 0.546 inches |
| Body Length: |
| 0.875 inches |
| Body Width: |
| 0.460 inches |
| Body Height: |
| 0.296 inches |
| Case Material: |
| Metal |
| Unthreaded Mounting Hole Diameter: |
| Between 0.136 inches and 0.140 inches |
| Actuator Length: |
| 0.468 inches |
| Actuator Height: |
| 0.344 inches |
| Actuator Width: |
| 0.218 inches |
| Actuator Position-action Relationship: |
| Left position maintained and right position maintained |
| Actuator Color: |
| Black single actuator |
| Maximum Voltage Rating In Volts: |
| 125.0 ac and 125.0 dc |
| End Application: |
| F16 op flt tr 36378 |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 2 pole, single throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 500.000 milliamperes resistive dc and 6.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 4 tab, solder lug |
| Shelf Life: |
| N/o |

NSN 5930-01-097-7275

Slide Switch - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A053a0