

View Online at <https://aerobasegroup.com/nsn/5930-01-097-8295>

Thread Class:

2b single mounting facility

Overall Length:

6.628 inches

Overall Height:

3.000 inches

Overall Width:

3.000 inches

Overall Diameter:

3.250 inches

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.180 inches single mounting facility

End Application:

Item is used on m/g controller model d21512 aboard 270 ft class coast guard vessels

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded hole single mounting facility

Cubic Measure:

6.000 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.156 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Contact Load Current Rating:

6.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Circular wafer, panel mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0