

View Online at <https://aerobasegroup.com/nsn/5930-01-097-8295>

**Thread Class:**

2b single mounting facility

**Overall Length:**

6.628 inches

**Overall Height:**

3.000 inches

**Overall Width:**

3.000 inches

**Overall Diameter:**

3.250 inches

**Individual Section Quantity:**

4

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.180 inches single mounting facility

**End Application:**

Item is used on m/g controller model d21512 aboard 270 ft class coast guard vessels

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Method:**

Threaded hole single mounting facility

**Cubic Measure:**

6.000 cubic inches

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.156 inches single mounting facility

**Contact Voltage Rating In Volts:**

600.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

6.0 amperes resistive load highest ac voltage rating at sea level

**Style Designator:**

Circular wafer, panel mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0