

View Online at <https://aerobasegroup.com/nsn/5930-01-097-9517>

**Thread Class:**

3a single pressure connection

**Overall Length:**

Between 2.500 inches and 3.000 inches

**Overall Diameter:**

0.890 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

**Mounting Method:**

Input port

**Features Provided:**

Hermetically sealed case

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4500.00 pounds per square inch gage

**Thread Size:**

0.563 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

7500.00 pounds per square inch gage

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

825.00 actuation point pounds per square inch gage and 475.00 deactuation point pounds per square inch gage and 325.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

29.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Test Data Document:**

81349-mil-s-9395 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf single pressure connection

**Specification Data:**

81349-mil-s-9395/31 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0