

View Online at <https://aerobasegroup.com/nsn/5930-01-097-9525>

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

0.900 inches

**Overall Height:**

0.950 inches

**Overall Width:**

0.600 inches

**Bushing Length:**

0.150 inches

**Body Width:**

0.600 inches

**Body Height:**

0.640 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.150 inches

**Actuator Height:**

0.160 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

1240-01-062-3543

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

20.0 ounces

**Switch Actuating Force:**

28.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.010 overtravel inches and 0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 4.000 amperes resistive ac and 3.000 amperes inductive ac and 1.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0