

View Online at <https://aerobasegroup.com/nsn/5930-01-097-9525>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

0.900 inches

Overall Height:

0.950 inches

Overall Width:

0.600 inches

Bushing Length:

0.150 inches

Body Width:

0.600 inches

Body Height:

0.640 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.150 inches

Actuator Height:

0.160 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

1240-01-062-3543

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

20.0 ounces

Switch Actuating Force:

28.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.010 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 4.000 amperes resistive ac and 3.000 amperes inductive ac and 1.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0