NSN 5930-01-098-0010

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-098-0010

Body Style: Bushing/hole mounted Hazardous Locations/environmental Protection: Dustproof Overall Length: 0.600 inches Overall Height: 1.078 inches Overall Width: 0.500 inches Bushing Length: 0.150 inches Body Length: 0.510 inches
Hazardous Locations/environmental Protection: Dustproof Overall Length: 0.600 inches Overall Height: 1.078 inches Overall Width: 0.500 inches Bushing Length: 0.150 inches Body Length:
Dustproof Overall Length: 0.600 inches Overall Height: 1.078 inches Overall Width: 0.500 inches Bushing Length: 0.150 inches Body Length:
Overall Length: 0.600 inches Overall Height: 1.078 inches Overall Width: 0.500 inches Bushing Length: 0.150 inches Body Length:
0.600 inches Overall Height: 1.078 inches Overall Width: 0.500 inches Bushing Length: 0.150 inches Body Length:
Overall Height: 1.078 inches Overall Width: 0.500 inches Bushing Length: 0.150 inches Body Length:
1.078 inches Overall Width: 0.500 inches Bushing Length: 0.150 inches Body Length:
Overall Width: 0.500 inches Bushing Length: 0.150 inches Body Length:
0.500 inches Bushing Length: 0.150 inches Body Length:
Bushing Length: 0.150 inches Body Length:
0.150 inches Body Length:
Body Length:
Body Width: 0.230 inches
Case Material:
Plastic
Actuator Style: Round
Actuator Diameter:
0.150 inches
Actuator Height: 0.160 inches
0.100 mg.100
Maximum Voltage Rating In Volts: 28.0 dc
End Application:
1240-01-062-3543
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
40
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:
1 two circuit, two positions momentary single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:

10.0 ounces

NSN 5930-01-098-0010

Sensitive Switch - Page 2 of 2



Δ	cti	Jato	r N	lov	em	en	ŧ.
м	CLI	uaic	JI IV	w	em		ш.

Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

8.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes motor dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0