NSN 5930-01-098-0010

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-098-0010

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.600 inches

Overall Height:

1.078 inches

Overall Width:

0.500 inches

Bushing Length:

0.150 inches

Body Length:

0.510 inches

Body Width:

0.230 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.150 inches

Actuator Height:

0.160 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

1240-01-062-3543

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 two circuit, two positions momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

10.0 ounces

NSN 5930-01-098-0010

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

8.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes motor dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0