## NSN 5930-01-098-0400



Sensitive Switch - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5930-01-098-0400 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.188 inches **Body Length:** 0.510 inches **Body Width:** 0.200 inches **Body Height:** 0.350 inches **Unthreaded Mounting Hole Diameter:** 0.088 inches **Actuator Style:** Round **Actuator Diameter:** 0.063 inches **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, double throw, both positions maintained single switch unit **Switch Release Force:** 1.0 ounces **Switch Actuating Force:** 5.0 ounces **Actuator Movement:** Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc **Special Features:** Includes 3 springs rtv adhesive **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A053a0