

View Online at <https://aerobasegroup.com/nsn/5930-01-098-0747>

Inside Diameter:

0.108 inches all connections and 0.113 inches all connections

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

2.750 inches

Overall Height:

1.060 inches

Overall Width:

1.310 inches

Body Length:

1.620 inches

Body Height:

1.060 inches

Unthreaded Mounting Hole Diameter:

Between 0.198 inches and 0.204 inches

Longest Horizontal Distance Between Mounting Centers:

1.062 inches

Longest Vertical Distance Between Mounting Centers:

1.062 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -50.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Base and unthreaded hole

Features Provided:

Electrical box connector

Contact Action Stimulus:

Increase

Proof Pressure:

225.00 pounds per square inch gage

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

375.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

500.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

164.00 actuation point pounds per square inch gage and 149.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Plain, unthreaded internal all connections

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0