NSN 5930-01-098-0756

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-098-0756

Thread Class:
2a single threaded bushing
Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
2.595 inches
Body Diameter:
0.665 inches
Body Length:
1.500 inches
Tempurature Sensing Element Type:
Bulb
Width Across Flats:
1.000 inches
Operating Tempurature Rating:
Between -50.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Threaded bushing
Features Provided:
Electrical box connector
Thready Qty Per Inch (tpi):
16 single threaded bushing
Contact Action Stimulus:
Increase
Thread Size:
0.750 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
238.00 actuation point degrees fahrenheit and 208.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage

60.0 first voltage

Frequency In Hertz:

Media For Which Designed:

Liquid

NSN 5930-01-098-0756

Thermostatic Switch - Page 2 of 2



Style	Design	nator:

Cylindrical w/flange

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0