

View Online at <https://aerobasegroup.com/nsn/5930-01-098-0759>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.313 inches single actuator

Overall Diameter:

1.000 inches

Individual Section Quantity:

5

Nonturn Device Type:

Tab at 3: 00 o'clock

End Application:

6625-01-077-6715

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

6 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+0.500/+12.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

550.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Rotor blades and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0