

View Online at <https://aerobasegroup.com/nsn/5930-01-098-0762>

Thread Class:

2a single mounting facility

Thread Length:

0.470 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.340 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.190 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.530 inches single actuator

Overall Diameter:

2.000 inches

Individual Section Quantity:

3

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section rear

Throw Quantity:

2 each section front

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.046 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from contact position 1 single actuator

Rotor Through Connection Quantity:

4 each section

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level and 10.0 amperes inductive load ac at sea level

Precious Material And Location:

Flat washer surfaces and contacts silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0