

View Online at <https://aerobasegroup.com/nsn/5930-01-098-1636>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Width Between Flats:

0.183 inches single actuator and 0.187 inches single actuator

Overall Length:

Between 1.358 inches and 1.408 inches

First Flat Length:

0.219 inches single actuator and 0.249 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.316 inches single actuator and 0.346 inches single actuator

Overall Diameter:

1.000 inches

Individual Section Quantity:

1

Operating Temperature Range:

-65.0/+125.0 degrees celsius

End Application:

An/prc-70 80058

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, parallel flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+1.000/+25.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

50.0 milliamperes resistive load ac at altitude

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0