

View Online at <https://aerobasegroup.com/nsn/5930-01-098-1636>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Width Between Flats:**

0.183 inches single actuator and 0.187 inches single actuator

**Overall Length:**

Between 1.358 inches and 1.408 inches

**First Flat Length:**

0.219 inches single actuator and 0.249 inches single actuator

**Shaft Diameter:**

0.247 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.316 inches single actuator and 0.346 inches single actuator

**Overall Diameter:**

1.000 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**End Application:**

An/prc-70 80058

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, parallel flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Detent Rotational Torque Range:**

+1.000/+25.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

50.0 milliamperes resistive load ac at altitude

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0