

View Online at <https://aerobasegroup.com/nsn/5930-01-098-3240>

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

2.637 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.215 inches single actuator and 0.223 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

Between 1.155 inches and 1.185 inches

Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 3:00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

195.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+12.000/+60.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level and 200.0 milliamperes inductive load dc at sea level

Precious Material And Location:

Contacts, rotor and terminals silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0