

View Online at <https://aerobasegroup.com/nsn/5930-01-098-3242>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.315 inches single mounting facility

**Overall Length:**

2.343 inches

**Overall Width:**

1.187 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.285 inches single actuator

**Nonturn Device Radius:**

0.375 inches at 3:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section front

**Throw Quantity:**

5 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

3 single section

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, breakoff single actuator

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material:**

Gold and silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0