

View Online at <https://aerobasegroup.com/nsn/5930-01-098-3243>

Thread Class:

2a single mounting facility

Thread Length:

0.315 inches single mounting facility

Overall Length:

2.343 inches

Overall Width:

1.187 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.285 inches single actuator

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

6 single section front

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

6 single section

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, breakoff single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material:

Gold and silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0