## NSN 5930-01-098-3246

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-098-3246

| Body Style:   |
|---|
| Hole mounted  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.500 inches  |
| Body Length:  |
| 0.780 inches  |
| Body Width:   |
| 0.250 inches  |
| Body Height:  |
| 0.440 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.088 inches  |
| Switch Actuator Quantity:   |
| 1   |
| Actuator Length:  |
| 0.120 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Height:  |
| 0.093 inches  |
| Actuator Width:   |
| 0.120 inches  |
| Actuator Free Position Height:  |
| 0.437 inches  |
| Maximum Voltage Rating In Volts:  |
| 16.5 dc   |
| Actuator Movement:  |
| 0.050 pretravel inches  |
| Contact Load Current Rating At Maximum Rated Voltage:                     |
| 1.000 amperes resistive dc  |
| Special Features:   |
| Push to talk bracket  |
| Terminal Type And Quantity:   |
| 4 solderless lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| Yes - demil/mli   |
| Fiig:   |

. . .

A053a0