NSN 5930-01-098-4071

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-098-4071

Hazardous Locations/environmental Protection:
Weatherproof
Overall Height:
0.375 inches
Body Height:
0.278 inches
Overall Diameter:
0.426 inches
Unthreaded Mounting Hole Diameter:
Between 0.040 inches and 0.060 inches
Distance Between Mounting Facility Centers:
0.218 inches
End Application:
6605 ins 99974
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
93.0 degrees celsius and -18.0 degrees celsius
Mounting Method:
Terminal and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
2.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
186.00 actuation point degrees fahrenheit and 197.00 actuation point degrees fahrenheit and 183.00 deactuation point degrees fahrenhei
and 194.00 deactuation point degrees fahrenheit and 3.00 differential point degrees fahrenheit
Contact Voltage Rating In Volts:
30.0 dc at sea level second voltage
Frequency In Hertz:
60.0 first voltage
Media For Which Designed:
Gas

Contacts gold

Precious Material And Location:

NSN 5930-01-098-4071

Thermostatic Switch - Page 2 of 2



Precious Material:
Gold
Style Designator:
Disc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A048b0