

View Online at <https://aerobasegroup.com/nsn/5930-01-098-4071>

Hazardous Locations/environmental Protection:

Weatherproof

Overall Height:

0.375 inches

Body Height:

0.278 inches

Overall Diameter:

0.426 inches

Unthreaded Mounting Hole Diameter:

Between 0.040 inches and 0.060 inches

Distance Between Mounting Facility Centers:

0.218 inches

End Application:

6605 ins 99974

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

93.0 degrees celsius and -18.0 degrees celsius

Mounting Method:

Terminal and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

186.00 actuation point degrees fahrenheit and 197.00 actuation point degrees fahrenheit and 183.00 deactuation point degrees fahrenheit and 194.00 deactuation point degrees fahrenheit and 3.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Style Designator:

Disc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0