NSN 5930-01-098-7296

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-098-7296			
Body Style:			
Bushing mounted			
Hazardous Locations/environmental Protection:			
Corrosion resistant			
Overall Length:			
1.156 inches			
Overall Height:			
1.613 inches			
Overall Width:			
0.375 inches			
Bushing Length:			
0.375 inches			
Body Length:			
0.781 inches			
Body Width:			
0.375 inches			
Body Height:			
0.957 inches			
Case Material:			
Metal			
Actuator Diameter:			
0.156 inches			
Actuator Height:			
0.281 inches			
Actuator Color:			
Natural single actuator			
Maximum Voltage Rating In Volts:			
115.0 ac and 28.0 dc			
End Application:			
Af sat com 13499			
Inclosure Type:			
Fully enclosed			
Mounting Method:			
Threaded bushing			
Thready Qty Per Inch (tpi):			
40			
Thread Size:			
0.250 inches			
Nonpile-up Contact Arrangement:			
2 two circuit, double make, two positions momentary single switch unit			
Contact Load Current Rating At Maximum Rated Voltage:			
10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000			

amperes inductive ac and 3.000 amperes lamp ac

NSN 5930-01-098-7296

Push Switch - Page 2 of 2



Thread	Series	Designator
Uns		

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0